


Product family: Uninsulated terminals - End-sleeves

Code: 01501, 01502, 01503, 01504, 01505, 01506, 01507, 01508, 01509, 01510, 01511, 01512, 01513, 01514, 01515, 01516, 01517, 01518, 01519, 01520, 01521

Description: UNINSULATED · SINGLE CABLE

Image:

Techinal Drawing:



Specifications:

TERMINAL MATERIAL: tinned copper

OPERATING TEMPERATURE: from -50 °C to 150 °C

ACCORDING TO STD.: DIN 46228-1 (tubular ferrules without plastic sleeve)

Code	Section (mm²)	Section (AWG/MCM)	Section not foreseen by DIN ()	L1 (mm)	L2 (mm)	D1 (mm)	D2 (mm)	S1 (mm)	
01501	0,5	(22)		6	5,3	2,1	1	0,15	
01502	0,75	(20)		6	5,3	2,3	1,2	0,15	
01503	1	(18)		10	9,3	2,5	1,4	0,15	
01504	1,5	(16)		7	6	2,8	1,7	0,15	1000/10000
01505	1,5	(16)		10	9	2,8	1,7	0,15	
01506	2,5	(14)		7	6	3,4	2,2	0,15	
01507	2,5	(14)		12	11	3,4	2,2	0,15	
01508	4	(12)		9	8	4	2,8	0,2	500/5000
01509	4	(12)		12	11	4	2,8	0,2	
01510	6	(10)		12	11	4,7	3,5	0,2	
01511	6	(10)		15	14	4,7	3,5	0,2	250/2500
01512	10	(8)		15	13,8	5,8	4,5	0,2	
01513	10	(8)		18	16,8	5,8	4,5	0,2	200/2000
01514	16	(6)		15	13,5	7,5	5,8	0,2	100/1000
01515	16	(6)		18	16,5	7,5	5,8	0,2	
01516	25	(4)		18	16	9,5	7,3	0,2	100/500
01517	35	(2)		18	16	11	8,3	0,2	
01518	50	(1)		25	22	13	10,3	0,3	100/300
01519	70	(2/0)	√	30	28	13,5	12,5	0,5	
01520	95	(3/0)	√	30	28	17,5	14,5	0,5	100/100
01521	120	(4/0)	√	30	28	19,5	17	0,5	